

### **INTRODUCING THE CLUB CAR 411**

Compact, Electric, Versatile

The Club Car 411 utility vehicle is the compact all-electric vehicle designed with your campus in mind. Ideal for low-speed logistics and cargo services, it fills the gap between full-sized trucks and small utility carts, soon to be the MVP of your campus fleet.

### COMFORTS THAT GET THE JOB DONE

The 411 LSV replaces a full-sized truck, but it doesn't leave the comforts behind. Unlike many utility vehicles, the 411 sports lockable doors, a back-up camera, radio, and the real music to your crew's ears, ventilation and heat.





Choose from a van box, pickup or flatbed design to customize your utility vehicle to your work.



# POWER TO PERFORM, ECONOMICALLY

The 411 LSV's powerful all-electric motor has the range to handle a full day's work and recharge overnight.

Equipped with a 13.4 HP motor, and up to 1,246 lbs (565 kg) payload capacity the Club Car 411 has the power to tackle any job so you can do your best work.

#### CLUB CAR 411 - DESIGNED FOR YOUR WORK DAY

In addition to its cargo capacity, the 411 has numerous other features designed to get the job done efficiently and comfortably.

- Power-assist steering
- 4-wheel hydraulic disc brakes
- Standard backup camera
- · Cabin heat and ventilation
- LCM display Speedometer, battery health, FM radio
- Optional GPS locator with alerts, and geofencing

In addition, the 411 LSV meets low-speed vehicle compliant safety standards for the U.S. and Canada, comes with a Vehicle Identification Number (VIN) and once registered, can be driven on roads posted 35 mph or less.



Learn more about Club Car 411 by visiting clubcar.com or by reaching out to your local Club Car representative.

## CLUB CAR 411 LSV & NON LSV







FLAT BED

PICK UP

VAN BOX

DIMENSIONS  LENGTH  WIDTH  HEIGHT  CURB WEIGHT		Length: 146 in. / 370.8 cm / 12' 2" Width: 55 in. / 139.7 cm / 4' 7"		
WIDTH		<del></del>		
HEIGHT		Width: 55 in. / 139.7 cm / 4' 7"		
		Width: 55 in. / 139.7 cm / 4' 7"		
CURB WEIGHT	Height: 75 in. / 190.5 cm / 6' 3"			
	2,039 lbs / 924 kg	2,090 lbs / 948 kg	2,200 lbs. / 997 kg	
PAYLOAD	<b>LSV:</b> 850 lbs / 386 kg <b>Non LSV</b> : 1,246 lbs / 565 kg	<b>LSV:</b> 795 lbs / 360 kg <b>Non LSV:</b> 1,195 lbs / 542 kg	<b>LSV:</b> 685 lbs. / 310 kg <b>Non LSV:</b> 1,085 lbs. / 492 kg	
PERFORMANCE	1011 2011 iji 10 iso / 000 iig	1011 2011 (,,i.de 1.50 / 0 1.2 l.g	1001 2001 (,000 100.7 102 llg	
TOP SPEED	<b>LSV:</b> Up to 25 mph / 40 km/h <b>Non LSV:</b> Up to 20 mph / Up to 32 km/h			
GRADE	Up to 22%			
TURNING RADIUS	157 in. / 3.9 m / 13' 1"			
ACCELERATION	0 - 20 mph in > 6 seconds / 0 - 32 km/h in > 6 seconds			
BRAKING DISTANCE	25 ft. @ 25 mph / 7.6 m @ 40 km/h / Best in Class			
SPECIFICATIONS				
RANGE	Up to 50 mi. / 80 km			
RECHARGE	Up to 6-8 hours / 110V/15A			
WARRANTY - VEHICLE	2 years*			
WARRANTY - BATTERIES	2 years*			
EQUIPMENT				
BACKUP CAMERA	Standard			
LCM DISPLAY	Standard / 7 in. / 17.7 cm			
PARKING BRAKE - MANUAL	Standard			
BODY PANELS	Reinforced ABS / Corrosion-resistant			
CABINAIR	Heating + Ventilation			
MOTOR				
MOTOR	10 Kw			
HORSEPOWER	13.4 HP			
MOTOR CONTROLLER	240A AC Controller			
DRIVE SYSTEM	2-wheel Rear Wheel Drive			
BED OPTIONS				
DIMENSIONS	47.5 in. / 120.6 cm Wide / 88 in. / 223.5 cm Length	53.25 in. / 135.8 cm Wide / 90 in. / 228.6 cm Length	53.5 in. / 135.8 cm Wide / 88 in. / 223.5 cm Length	
CARGO BOX VOLUME	/	/	123 sq. ft. / 11.43 sq. m	
BATTERIES				
ТҮРЕ	VRLA (120 Ah)			
VOLTAGE	72V			
NUMBER OF BATTERIES	6			
CAPACITY	8.64 kWh			
SAFETY				
CHASSIS	Reinforced Steel / Coated			
SUSPENSION	Front: Transverse Leaf Spring / Rear: Horizontal Spring with Coll-over Shock			
BRAKES	Disc / 4-wheel, Hydraulic			
STEERING	Power Assist			

LSV INCLUDES VIN AND MCO FOR TITLE AND REGISTRATION.

\*For details, consult User Manual. All prices, features, options, and specifications are subject to change without notice.

NON LSV FOR CLOSED CAMPUS APPLICATIONS ONLY. VEHICLE DOES NOT INCLUDE VIN OR MCO.
\*For details, consult User Manual. All prices, features, options, and specifications are subject to change without notice.

